

MATERIAL CERTIFICATE

SVITAP J.H.J.
Svitavy

Technical fabrics

PN 100 - 80 - 98
SKP 17.20.10

This material certificate is indivisible part of PN 100-80-98 and contains of constructional-
constructional-technological parametrs and values of applied chracteristics
of technical fabric.

Constructional-technological parameters

Type:

TERA

Warp:

	Units	Middle	Min.	Max.	Exam. method
Material Fineness	[Tex]	Cotton OE 29,5x2 tex			
Warp setting	[1 / cm]	26	25,5	27	ČSNEN 1049-2
Max. strenght	[N/5 cm]		750		ČSN EN ISO 13934-1
Ductility	[%]		13		ČSN EN ISO 13934-1

Weft:

Material Fineness	[Tex]	Cotton OEAI - S160 72 tex			
Warp setting	[1 / cm]	16	15,5	17,0	ČSNEN 1049-2
Max. strenght	[N/5 cm]		520		ČSN EN ISO 13934-1
Ductility	[%]		7		ČSN EN ISO 13934-1

Characteristics of fabric:

Binding	plain				
Weight:	[g / m2]	300	290	310	ČSN 800845
Width:	[cm]	to 100 incl. over 100	-1 -2	+1 3	
Thickness:	[mm]	0,7	0,7	0,9	ČSN EN ISO5084
Water column	[cm]	23			
Finishing:		dyed			

Notation:

Effectivity: 2008-05-05

Disposed by: Ing. Pavlína Hazuchová

Carried by: Jana Pražanová

Following:

SVITAP J.H.J. spol. s r.o.
Kijevska 8
CZ 568 02 SVITAVY
IČO: 465 09 755 VAT: CZ46509755

MATERIAL CERTIFICATE

SVITAP J.H.J.
Svitavy

Technical fabrics

PN 100 - 80 - 98
SKP 17.20.10

This material certificate is indivisible part of PN 100-80-98 and contains of constructional-
constructional-technological parametrs and values of applied chracteristics
of technical fabric.

Constructional-technological parameters

Type:

TERA

Warp:

	Units	Middle	Min.	Max.	Exam. method
Material Fineness	[Tex]	100 % cotton OE 29,5x2 tex			
Warp setting	[1 / cm]	25,8	25,3	26,8	ČSNEN 1049-2
Max. strenght	[N/5 cm]		706		ČSN EN ISO 13934-1
Ductility	[%]		13		ČSN EN ISO 13934-1

Weft:

Material Fineness	[Tex]	100% cotton OE 72 tex			
Warp setting	[1 / cm]	16,2	15,7	17,2	ČSNEN 1049-2
Max. strenght	[N/5 cm]		508		ČSN EN ISO 13934-1
Ductility	[%]		7		ČSN EN ISO 13934-1

Characteristics of fabric:

Binding	plain				
Weight:	[g / m2]	303	273	333	ČSN 800845
Width:	[cm]	to 100 incl. over 100	-1 -2	+1 3	
Thickness:	[mm]	0,6	0,5	0,7	ČSN EN ISO5084
Finishing:		dyed, hydrophobe, fungicide			

Notation:

Water column 16 cm - ČSN EN 20811

Fungicide finishing - DIN 53 931

Effectivity: 2012-05-02

Disposed by: Ing. Vaverová Zdeňka

Carried by: Ing. Jaroslav Malý



Following:

SVITAP J.H.J. spol. s r.o.
Kijejská 8 -56-
CZ 568 02 SVITAVY
IČO: 465 09 755 VAT: CZ46509755